

Tender Document

for Supply & Installation of Desktop Computers, Routers, Switches Printers & Other Peripherals At

The Calicut Co-operative Urban Bank Ltd.



Tender Document No. CCUB/Edp/Tender-01/2018-19 Dated: 17th July, 2018

ISSUED BY

The Calicut Co-operative Urban Bank Ltd. CCUB Building, Kallai Road, Chalappuram P.O., Kozhikode - 673002 Tel No. 0495-2307200 & 2307225 Email : <u>calicuturban@gmail.com</u> Website: <u>www.calicuturbanbank.com</u>

IN	DE	X
T T 4		× •

Sl. No.	Contents	Page No.
01.	Bid Information Sheet	3
02.	Introduction	4
03.	Bid information and Instructions to Bidders	24
04.	Specification Details	16
05.	Letter of Acceptance	24
	oroperio	
	dicul	
C	aicut conserior	

01.Bid Information Sheet

Document Description	Tender Document for "Supply & installation of Desktop Computers, Printers, Routers, Switches, Ups, and other peripherals at Calicut Co- operative Urban Bank Ltd.
Tender Document No.& Date	CCUB/Edp/Tender-1/2018-19 Dt. 17-07-2018
Last date & Time of Submission of Response to Tender Document	23-07-2018 (14:00 Hrs)
Bid Opening (Techno-Commercial)	24-07-2018
Declaration of bidders qualified for opening commercial bid	To be declared later
Validity of Tender	180 (One hundred and eighty) days from the date of opening of tender
Cost of Tender Document (non- refundable)	Free
Processing Fee (non-refundable)	₹ 250/- + GST @18% to be submitted by cash or in the form of DD/Pay Order along with the response to Tender Document in favor of "The Calicut co- operative Urban Bank Ltd.", payable at Kozhikode.
Bid Security/EMD	Minimum 7% of Quoted amount or a maximum of Rs.40,000/- in the form of Demand Draft/Pay order in favor of the Calicut Co-operative Urban Bank Ltd. Payable at Kozhikode.
Name, Designation, Address and other details (For Submission of Response to Tender Document)	General Manager, The Calicut co-operative Urban Bank Ltd., Head Office, Kallai Road, Chalappuram P.O., Kozhikode – 673002. Tel. No. 495 – 2307200 & 20307225 e requested to remain updated for any notices /

<u>Important Note:</u> Prospective Bidders are requested to remain updated for any notices / amendments / clarifications etc. to the Tender Document through phone and Email. So you are requested to provide the mobile number & Email ID in front of bid cover.

2. Introduction

2.1. Objective :

- 2.1.1. The Calicut Co-operative Urban Bank Ltd. (hereinafter called "CCUB") is a Reserve Bank licensed urban bank with 103 year of banking experience. The Bank has started Computerisation in 1998 onwards.
- **2.1.2.** To improve the bank's IT infrastructure, ccub plans to procure Desktop Computers, Printers, Routers, Switches and Other Peripherals.

2.2. Document Purpose

2.2.1. Purchase of Desktop Computers, Printers, Switches, Routers and other peripherals are required to fulfill IT infrastructure need of CCUB.

3. Bid Information and Instructions to Bidders

3.1. Obtaining Tender Document, Processing Fee

- **3.1.1.** The Tender Document can be downloaded free of cost from the website of CCUB, www.calicuturbanbank.com from the date mentioned in the Bid Information Sheet.
- **3.1.2.** Prospective Bidders interested to participate in the bidding process are required to submit their Project proposals in response to this Tender Document along with a non-refundable processing fee as mentioned in Bid Information Sheet. A Bidding Company will be eligible to participate in the bidding process only on submission of Bid processing fee.
- **3.1.3.** The bids submitted without Processing Fee shall not be considered for the bidding and such bids shall not be opened by CCUB.
- 3.1.4. It may be noted that CCUB will not pay any amount / expenses / charges / fees / traveling expenses / boarding expenses / lodging expenses / conveyance expenses / out of pocket expenses, regardless of the conduct or outcome of the Tendering process.

3.2. Bid Submission date and Bid Opening date

- **3.2.1.** The bidding methodology adopted for this Project shall be Single stage Two envelop system i.e. The Bidders shall submit their Project proposal (Both Techno-Commercial and Financial Bid same time in separate sealed envelopes) in line with this Tender Document.
- **3.2.2.** The last date for submission of bids is as mentioned in the Bid Information Sheet. No bids shall be accepted after the date and time mentioned above.
 - 4 The Calicut Co-operative Urban Bank Ltd.

- **3.2.3.** Techno-Commercial bids shall be opened on the same day as mentioned in the Bid Information Sheet.
- **3.2.4.** Date of opening of financial bids shall be informed by phone/email, after short listing of eligible Bidders based on Techno-Commercial bid evaluation.

3.3. Minimum Eligibility Criteria

- **3.3.1.** General Eligibility:
- The bidder must have completed at least 5 years of experience/operation in the field of supply, installation and support of Desktop Computers and Printers.
- ii. The bidder should be OEM or authorized Dealers/ Channel partners/ Distributors of reputed brand having authorization for sales and after sales support for Desktop Computers Printers and other Devices (enclose OEM certificate/letter specific for this tender).
- **3.3.2.** Financial Capability.
- i. Turn over should be minimum 40 lakhs for either FY 2017-18 or average of three financial years FY 2015-16, 2016-17 and 2017-18. In case the audited annual accounts for the year 2017-18 are not available with the bidder, turnover shall be considered for the FY 2016-17 or average of three financial years FY 2014-15, 2015-16 and 2016-17.

3.3.3. Experience:

i.

The bidder should have successfully executed at least three contracts of similar nature (supply and installation of minimum 15 desktop computers in each contract) within the past three years as on 30-June-2018.

3.4. Documents to be signed and submitted by Bidders

i. When the work is bid for by a company/organization, the bid shall be signed by the individual legally authorized to enter into commitments on their behalf. Only one submission of response to Tender Document by each bidder will be permitted.

- ii. The documents required under the tender conditions for submission along with the tender are listed below. The bidder/s are advised to examine the various conditions and submit necessary documents accordingly. In case of non-submission of any of the desired information, the bid may be considered non-responsive and are liable to be rejected outright.
- 3.4.1. Basic documents:
- i. Processing Fee and Bid Security/EMD.
- ii. Letter of authorization in favor of the person to sign this tender and represent his/her company for this contract.
- iii. Duly signed and stamped Tender Document (amendments if any) by the Authorized signatory
- **3.4.2.** Documents in Support of Eligibility:
- i. Copy of VAT/Sales Tax/GST registration certificate, and PAN.
- ii. Self-attested copies of supply order and their respective completion certificates issued by clients for similar orders during last 3 years.
- iii. Certificate by Statutory Auditor / Practicing Chartered Accountant of the Bidding Company in support of turnover along with audited copies of annual accounts for all the FYs in support of financial capability.
- A copy of Authorization letters issued by each different OEM of proposed items in Technical Bid to Authorized Distributors/ Partners/ Dealers to participate in the bid and for support to after sale service specific to tender. Non submission of these certificates will result rejection of submitted bid.

Note:

a. Compliance with the minimum eligibility criteria mentioned above should be indicated item-wise in a separate sheet with the page number of the supporting document (in the following format).

Sl. No.	Eligiblity Criteria	Compliance	Reference of
		(Yes/No)	Enclosed Proof
			(page nos.)

b. CCUB reserves the right to verify/confirm all original documentary evidence submitted by the bidder in support of above mentioned clauses of eligibility criteria.

3.5. Validity of the Response to Tender Document

The Bidder shall submit the response to Tender Document which shall remain valid up to one hundred and eighty (180) days from the date of opening of tender ("Bid Validity"). CCUB reserves the right to reject any response to Tender Document which does not meet the aforementioned validity requirement. CCUB may solicit the bidders' consent to an extension of the validity period of the bid. The request and the response shall be made in writing.

3.6. Selection of successful Bidder

After bid opening, Techno-commercial bids submitted by those Bidders who have furnished the processing fee and EMD shall be evaluated by CCUB on the basis of Minimum Eligibility Criteria stipulated in clause 2.3.

3.7. Earnest Money Deposit (EMD)

- **3.7.1.** The bidder shall be required to submit a sum as specified in the Bid Information Sheet as Earnest Money Deposit, for keeping the offer open till such date as might be specified in the tender. Bids not accompanied with earnest money deposit as provided in the Bid Information Sheet shall be summarily rejected.
- **3.7.2.** It shall be understood that the Tender Document has been issued to the bidder and the bidder is permitted to bid in considerations of the stipulation on his/her part, that after submitting his/her bid, he/she will not withdraw from his offer or modify the terms and conditions thereof in a manner not acceptable to ccub.
- **3.7.3.** Should the bidder fail to observe or comply with the said stipulation, the EMD amount shall be liable to be forfeited
- **3.7.4.** The EMD of the successful bidder will be returned on submission of Performance Bank Guarantee as defined in this Tender Document and obtaining confirmation.

- **3.7.5.** The EMD of the unsuccessful bidders shall be returned to them within one month of issue of Letter of Acceptance to the successful bidder. But no interest will be payable thereon.
- **3.7.6.** In case it is found that, the bidder/s has furnished misleading/wrong or fraudulent information / documents or information furnished by them is not found to be true, the Earnest Money of the bidder/s will be forfeited.
- **3.7.7.** In case the bidder withdraws the bid before financial bid opening, then the EMD of the respective bidder shall be forfeited.

3.8. Structuring of Bid Selection Process:

Two envelop system has been envisaged under this Tender Document i.e. Bidders have to submit both Techno-commercial bid and financial bid together in response to this Tender Document in separate sealed envelopes. Bids not accompanied without EMD and processing fee will be summarily rejected. In the first stage, Techno-commercial bids shall be evaluated as per Minimum Eligibility Criteria and acceptability of technical specification for Desktop Computers Printers and Other Devises separately and the list of short listed Bidders shall be intimated. In the second stage, financial bids submitted by the short-listed Bidders shall be opened in presence of their representative who choose to attend based on which lowest will be considered as successful bidder.

3.9. Financial Bid

- **3.9.1.** The prices quoted in the financial bid should be without any conditions.
- **3.9.2.** The price bid must be filled in completely, without any error, erasures or alterations.
- **3.9.3.** The prices should be mentioned in Indian Rupees only in clearly readable format without any overwriting.
- **3.9.4.** The Financial bid shall be on a fixed price basis and, no price variation on any account shall be considered.
- **3.9.5.** Price quotation accompanied by vague and conditional expression such as "subject to immediate acceptance", "subject to confirmation before sales", etc. will be treated as being at variance and shall be liable for rejection.
- **3.9.6.** The envelop consisting of Financial Offer shall be marked as "Financial Bid"
- **3.9.7.** Prices quoted shall be for the entire period of Contract.
 - 8 The Calicut Co-operative Urban Bank Ltd.

- **3.9.8.** It is the responsibility of the Bidder to clearly identify all costs associated with any item or series of items in this Tender Document and submit the total cost in the financial bid.
- **3.9.9.** The financial bid should include incidental charges and customization charges if any.
- **3.9.10.** The bidder shall ensure that there is no discrepancy in the rates mentioned in figures and words. In case of any discrepancy, the small rate mentioned in the bid shall be taken as final and binding.
- **3.9.11.** In the event of arithmetic calculation mistake, the individual price in words shall be considered for calculation.
- **3.9.12.** The bidder must fill and submit the rates as per instructions given above. If the bidder does not quote a price/rate for any item in the Form of Bid, his tender may be summarily rejected.

3.10. Non Transferable Bid

Neither the contract nor any rights granted under the contract may be sold, leased/sublet, assigned, or otherwise transferred, in whole or in part, by the vendor, and any such attempted sale, lease, assignment or otherwise transfer shall be void and of no effect. The vendor shall not subcontract or permit anyone other than its personnel to perform any of the work, service or other performance required of the vendor under the contract.

3.11. Deviations

The bidder should clearly read and understand all the terms and conditions, specifications, etc. mentioned in the original tender documents. If the bidder has any observations, the same may be indicated in his forwarding letter along with the bid. Bidders are advised not to make any corrections, additions or alterations in the original tender documents. If this condition is not complied with, tender is liable to be rejected.

3.12. Deadline for submission of bid

The bid duly filled must be received by CCUB at the address specified, not later than the date and time mentioned in the "Bid Information Sheet". Bid received later than the deadline prescribed for submission of tender by ccub will be rejected.

3.13. Withdrawal of bid

No Tender can be withdrawn after submission and during tender validity period. Submission of a tender by a bidder implies that he had read all the tender documents including amendments if any, visited the site and has made himself aware of the scope and specifications of the job to be done, local conditions and other factors having any bearing on the required job.

3.14. Sealing and marking of bids

All completed tender documents shall be sealed in an envelope superscribed with the name of the Bidder, the Tender Document Number and the name of package "Supply & Installation of Desktop Computers and Printers" or specify Item Names, as indicated in "Bid Information Sheet". In addition to the above, the envelope shall also contain the name, address and phone no. of the bidder.

3.15. Opening of the bid

Bids will be opened at the address mentioned in "Bid Information Sheet" in presence of bidders or authorized representatives of bidders who wish to attend the opening of tenders. Ccub reserves the right to open the bid/s even if only one bid is received.

Bidders or their authorized representatives who are present shall sign in register for evidence of their attendance.

3.16. Clarification of the bid

To assist the examination, evaluation and comparison of the tenders, ccub may at his discretion ask the bidders for any clarifications as considered essential. All such correspondence shall be in writing and no change in price or substance of the tender shall be either sought or permitted. Above clarification and their response shall form part of the tender and shall be binding on the bidder.

3.17. Examination of the bids

Ccub shall determine whether each bid is of acceptable quality, is generally complete and is substantially responsive to the bidding documents. For purposes of this determination, a substantially responsive bid is one that confirms to all the terms, conditions and specifications of

without material deviations, the bidding documents objections, conditionally or reservation. If a bid is not substantially responsive, it shall be rejected by the ccub. In case of tenders containing any conditions or deviations or reservations about contents of tender document, ccub may ask for withdrawal of such conditions/deviations/reservations. If the bidder does not withdraw such conditions/deviations/ reservations, the tender treated non-responsive. ccub's decision shall be as regarding responsiveness or non-responsiveness of a tender shall be final and binding.

3.18. Canvassing

No bidder is permitted to canvass to ccub on any matter relating to this tender. Any bidder found doing so may be disqualified and his bid may be rejected.

3.19. Right to accept any bid or reject all bids

Ccub reserves the right to accept, split, divide, negotiate, cancel or reject any bid or to annul and reject all bids at any time prior to the award of the contract without incurring any liability to the affected bidders or any obligation to inform affected bidder, the grounds of such action. If the bidder, as individual or as a partner of partnership firm, expires after the submission of his bid but before award of services, the ccub shall deem such bid as invalid.

3.20.

Award of Contract

CCUB shall issue LoA (Letter of Award) / Purchase Order in duplicate to the successful bidder in writing by a Registered Letter/Courier/Speed Post or per bearer. Duly signed and stamped duplicate copy of the letter has to be returned by the selected bidder within a week of receipt of letter as token of acknowledgement. Issuance of LoA/PO against an offer made shall constitute a legal and binding contract between ccub and the selected bidder.

3.21. Method of Submission

The response to Tender Document is to be in the following manner:-

3.21.1. "Covering Envelope" – Super scribed as "Covering Envelope containing Processing Fee, DD/Pay Order towards EMD" at the top of the Envelope; and "Name & Address of the Bidder" on the left hand side bottom;

It should be addressed to CCUB and shall contain:

- i. Covering Letter.
- ii. DD/Pay order towards the Bid Processing Fee.
- iii. EMD (DD/Pay Order)
- 3.21.2. "Techno-Commercial Envelope" Super scribed as "Technocommercial Proposal in response to Tender Document _____

(Mention the Tender Document No)" at the top of the Envelope; and "Name & Address of the Bidder" on the left hand side bottom;

(This envelope shall be sealed and shall contain the required documents as mentioned in Clause above along with Technical bid.)

3.21.3. "Financial Envelope" - Super scribed as "Financial Bid in response to Tender Document_____ (Mention the Tender Document No)" at the top of the Envelope; and "Name & Address of the Bidder" on the left hand side bottom;

It shall be sealed and shall contain :

- i. Tender Document_____
- ii. (Covering letter of Financial Proposal

<u>Important Note:</u> The Bidders shall not deviate from the naming and the numbering formats mentioned above, in any manner.

3.22. Right of CCUB to reject a Bid

CCUB reserves the right to reject any or all of the responses to Tender Document or cancel the Tender Document without assigning any reasons whatsoever and without any liability.

3.23. Cancellation of Contract

The CCUB reserves the right to cancel the contract of the selected bidder and recover expenditure incurred by the ccub on the following circumstances:

- **3.23.1.** The bidder has made misleading or false representations in the forms, statements, and attachments submitted in proof of the eligibility requirements.
- **3.23.2.** The selected bidder commits a breach of any of the terms and conditions of the bid/contract.
- **3.23.3.** The bidder goes into liquidation voluntarily or otherwise during the execution of contract.
- **3.23.4.** The progress regarding execution of the contract, made by the selected bidder is found to be unsatisfactory.
- **3.23.5.** After the award of the contract, if the selected bidder does not perform satisfactorily or delays execution of the contract, the ccub reserves the right to get the balance contract executed by another party of its choice by giving one month's notice for the same. In this event, the selected bidder is bound to make good the additional expenditure, which the ccub may have to incur to carry out bidding process for the execution of the balance of the contract. This clause is applicable, if for any reason, the contract is cancelled.

3.24. Important notes and instructions to Bidders

3.24.1. Wherever information has been sought in specified formats, the Bidders shall fill in the details as per the prescribed formats and shall refrain from

any deviations and referring to any other document for providing any information required in the prescribed format.

- **3.24.2.** If the Bidder conceals any material information or makes a wrong statement or misrepresents facts or makes a misleading statement in its response to Tender Document, in any manner whatsoever, ccub reserves the right to reject such response to Tender Document and/or cancel the Letter of Award, if issued and the EMD provided up to that stage shall be en-cashed. Bidder shall be solely responsible for disqualification based on their declaration in the submission of response to Tender Document.
- **3.24.3.** CCUB reserves the right to recover any dues payable by the selected bidder from any amount outstanding to the credit of the selected bidder, including the pending bills and/or invoking Bank Guarantee, if any, under this contract or any other contract/order.
- **3.24.4.** Response submitted by the Bidder shall become the property of the ccub and the ccub shall have no obligation to return the same to the Bidder. However, the EMDs submitted by unsuccessful Bidders shall be returned as specified in Clause above.
- **3.24.5.** All pages of the response to Tender Document submitted must be signed and stamped by the authorized person on behalf of the Bidder.
- **3.24.6.** Bidders may carefully note that they are liable to be disqualified at any time during bidding process in case any of the information furnished by them is not found to be true. The decision of CCUB in this respect shall be final and binding.
- **3.24.7.** The bidder must obtain for itself on its own responsibility and its own cost all the information including risks, contingencies & other circumstances in execution of the installation and commissioning. It shall also carefully read and understand all its obligations & liabilities given in tender documents.
- **3.24.8.** CCUB may at its discretion extend the deadline for submission of the bids at any time before the time of submission of the bids.
- **3.24.9.** Bidders shall mention the name of the contact person and complete address of the Bidder in the covering letter.
- **3.24.10.** Response to Tender Document that are incomplete, which do not substantially meet the requirements prescribed in this Tender Document, will be liable for rejection by ccub.
- 14 The Calicut Co-operative Urban Bank Ltd.

- **3.24.11.** Bidders delaying in submission of additional information or clarifications sought will be liable for rejection.
- **3.24.12.** Non submission and/or submission of incomplete data/ information required under the provisions of Tender Document shall not be construed as waiver on the part of CCUB of the obligation of the Bidder to furnish the said data/information unless the waiver is in writing.
- **3.24.13.** Only Kozhikode Courts shall have exclusive jurisdiction in all matters pertaining to this Tender.
- **3.24.14.** CCUB reserves the right to delete items from the schedule of requirements specified in the tender. Ccub also reserves the right to alter the quantity and vary specifications.
- **3.24.15.** CCUB reserves the right to make any changes in the terms and conditions of the tender.
- **3.24.16.** CCUB shall be under no obligation to accept the lowest or any other offer, including those received late or incomplete offers, without assigning any reason whatsoever.
- **3.24.17.** CCUB will not be obliged to meet and have discussions with any bidder, and or to listen to any representations.
- **3.24.18.** The bidder shall not make any addition or alteration in the tender documents. The requisite details should be filled in by the bidder wherever required in the documents. Incomplete tender or tender not submitted as per instructions is liable to be rejected.
- **3.24.19.** Bidders can bid for either any of the Group from A to I or Selective Groups or Total.
- **3.24.20.** The bidder shall collect all details required for installation / successful working of each equipment, from our Head Office. If the installation is not completed by the bidder, which shall be completed by bank and the expenses will be deducted from bidder's bill amount.
- **3.24.21.** The Biometric devises are required to be connect with our devises installed at our head office.
- **3.24.22.** The buyback amount shall be accounted as per norms. The amount shown as the buy back, which is required to be remit our Head office without deducting any charges/taxes.
- **3.24.23.** Bidder require a registered office at Kozhikode.
- 15 The Calicut Co-operative Urban Bank Ltd.

4. SPECIFICATION DETAILS & QUANTITY

4.1. Specification & Quantity

4.1.1. Group A: Commercial Enterprise Desktop Computer – 8 Nos.

Sl. No.	Category	Description	Nos.
01.	Make	Lenovo / HP/ Dell	5
	Processor	Intel Pentium Dual Core G-4560 – 3.5GHz 7 th	-
		Generation Processor with 3 MB L2 Cache	
	Chipset	Intel Chipset based Mother board	
	Memory	4 GB – DDR4 – 2400 MHz Memory Expandable to	
		32 GB (2 DIMM Slots)	
	Hard Disk	1 TB SATA HDD	
	Hdd Controller	4 Ports SATAController	
	Monitor/Display	LED Backlight Display TCO 6.00 Certified (Same	
	intointoi, Disping	make as PC)	
	Graphics	Intel HD Graphics	
	Keyboard	104 keys USB Keyboard (Same make as PC)	
	Mouse	USB Optical Mouse with 2 Button + Scroll (Same	
	Wouse	make as PC)	
	I/O Devices	6 USB Ports (2 x 3.0 in front, 2 x $3.0 + 2 x 2.0$ in	
		Rear)	
	OS Supports	Microsoft Windows and Linux OS	
	Operating System	Not required	
	Certifications	ISO 9001, ISO 14001, Energy Star, RoHS, EPEAT,	
	Contineations	etc	
	Ports	6 USB Ports, 1 Mic., 1 headphone in side, 1	
		Display Port	
	DVD ROM Drive	DVD RW Drive	
	Network	10/100/1000 Mbps Ethernet Onboard	
	Warranty	3 Years Onsite Comprehensive Manufacturer's	
	, N	Warranty	
02.	Make	Lenovo / HP/ Dell	03
	Processor	Intel Pentium Dual Core G-4560 – 3.5GHz 7 th	
		Generation Processor with 3 MB L2 Cache	
	Chipset	Intel Chipset based Mother board	
	Memory	4 GB - DDR4 - 2400 MHz Memory Expandable to	
		32 GB (2 DIMM Slots)	
	Hard Disk	1 TB SATA HDD	
	Hdd Controller	4 Ports SATAController	
	Monitor/Display	LED Backlight Display TCO 6.00 Certified (Same	
		make as PC)	
	Graphics	Intel HD Graphics	
	Keyboard	104 keys USB Keyboard (Same make as PC)	
	Mouse	USB Optical Mouse with 2 Button + Scroll (Same	
		make as PC)	
	I/O Devices	6 USB Ports (2 x 3.0 in front, 2 x 3.0 + 2 x 2.0 in	
		Rear)	
	OS Supports	Microsoft Windows and Linux OS	
	Operating System	Windows 10 Professional Preloaded	

16 The Calicut Co-operative Urban Bank Ltd.

Certifications	ISO 9001, ISO 14001, Energy Star, RoHS, EPEAT,	
Ports	etc 6 USB Ports, 1 Mic., 1 headphone in side, 1	
	Display Port	
DVD ROM Drive	DVD RW Drive	
Network	10/100/1000 Mbps Ethernet Onboard	
Warranty	3 Years Onsite Comprehensive Manufacturer's	
	Warranty	

4.1.2. Group B: Printers – 9 Nos.

Sl.	Category	Description	Nos.
No.			•
01.	Passbook Printers –	With 3 Years Onsite Comprehensive	2
	Epson PLQ 30	Manufacturer's Warranty including printer head	
02.	Dot Matrix Printers –	With 3 Years Onsite Comprehensive	7
	Epson FX 890 II (buy	Manufacturer's Warranty including printer head	
	back basis)	Buy back items:	
		Wep 800 dx $-$ 3 Nos.	
		Epson LQ1150 II – 2 Nos. \checkmark	
		Epson Fx 890 – 1 Nos.	
		Wep LQ 1050+DX – 1 Nos.	
03.	Laser Printers – Hp 1020	With 3 Years Onsite Comprehensive	2
	+	Manufacturer's Warranty	

4.1.3. Group C : Routers, Switches & UTM

Sl. No.	Category	Description	Nos.
01.	Router – CISCO C841M-	Cisco 800M Router 4 port GE LAN, 2 port GE	1
01.	4X/K9	WAN, 2 WIM Slots	1
		SOLN SUPP 8X5XNBD Cisco 800M Router 4 port	
		GE LAN, 2 port for 36 months	
		Blank faceplate for WIM slot on Cisco ISR 800M	
		Cisco 800M Router 1-Port Serial WAN Interface	
		Module	
		V.35 Cable, DTE Male to Smart Serial, 10 Feet	
	C	Cisco 800M ISR UNIVERSAL	
		Rack mounting Kit	
	\sim	AC Power Cord (India)	
		With 3 Years Onsite Comprehensive	
y		Manufacturer's Warranty	
02.	Switch – CISCO SG300	28 Port	1
		Rack mounting Kit	
		With 3 Years Onsite Comprehensive	
		Manufacturer's Warranty	
03.	UTM with Dongle	With 3 Years Onsite Comprehensive	1
	Fortinet 30E with 4 G	Manufacturer's Warranty	
	Dongle	General Requirements and Features	
		The Firewall must be appliance based	
		Licensing: should be per device license for unlimited	
		users for Firewall / VPN (IPSec & SSL) and other	

 features. There should not be any user/IP/host based licenses – Please specify if the product does not follow the required licensing policy. The device should be having security functions like fittering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. Intrusion prevention system, Traffic Gateway level antivirus, Antispam, Category based web filtering. The Firewall should be having minimum 900 Mbps filtroughput 150Gateway to Gateway and 200Clent-to-Cateway IPSec VPN throughput. Should support 70 Mbps IPSec VPN throughput. Test condition should be real-world / enterprise mix filt. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Entract protection throughput on Realworld or Entract protection throughput on Realworld or Should support Nirutal Damains). Please mention what is the stamium number of virtual instances support. Should support IPv6 functions such as Management over IPv6. IPv6 routing protocols, IPv6 nunciling free Strings Ind UTM for Pv6 furfic, NAT46, NAT64, IPv6 IPv6. IPv6. IPv6. IPv6 IPv6. IPv6. IPv6. IPv6. IPv6. IPv6. IPv6. Pv6 routing sequents the should be assed to Sp flood, TCP/UDP Sort factor, NAT64, IPv6. IP		
follow the required licensing policy. The device should be having security functions like Firewall, VPN (IPSec &SSL), Application frewall, Gateway level antivirus, Antispan, Category based web filtering, Intrusion prevention system, Traffic shaping, etc. The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to Gateway and 200Client-to-Gateway IPSec VPN Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, freewall and UTM for IPv6 fractions such as Management over IPv6, IPv6 routing protocols, Pv6 tunnelling, freewall and UTM for IPv6 fractions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, freewall and UTM for IPv6 fractions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, freewall and UTM for IPv6 fractions such as Management over IPv6, IPv6 for authentication for USPs, BCP, IS-IS, RIPng, OSPFv3 and BCP4		features. There should not be any user/IP/host based
 The device should be having security functions like Firewall, VPN (IPSec &SSL), Application firewall, Gateway level antivirus, Antispan, Category based web filtering, Intrusion prevention system, Traffic shaping, etc. The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput. Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to-Gateway and 200Client-to-Gateway IPSec VPN Trunnels The firewall should be real-world / enterprise mix traffic. The firewall should support a minimum of atleast 250 Mbps of IPS ± 150 Mbps NGFW Throughput. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic. Device should support IVrtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should Support IPv6 functions such as Management over IPv6. IPv6 routing protocols, IPv6 tunneling. firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should Support IPv6 functions such as Management over IPv6. IPs6 routing protocols, IPv6 tunneling. firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should Support IPv6 and IPv6 Rate based DOS protection with threshold setting against TCP Syn flood, TCP/UDP/ SCTP/ICMP session flooding. Threshold setting against CP Syn poot; eshould support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPF and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration 		
 Firewall, VPN (IPSec &SSL). Application firewall, Gateway level antivirus, Antispam, Category based web filtering, Intrusion prevention system, Traffic shaping, etc. The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 1 ISOGateway-to-Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & Services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000-signatures 		
Gateway level antivirus, Antispan, Category based web filtering, Intrusion prevention system, Traffic shaping, etc. The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput. Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to-Gateway and 200Client-to-Gateway IPSec VPN Trunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Thould support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic. Device should support nore than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 foruing protocols, IPv6 tunnelling, firewall and UTM for IPv6 raffic, NAT46, NAT64, IPv6 IPsEC VPN Should Support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP port scan, ICMP sweep, TCP/UDP SCTP/ICMP session flooding, Threshold settings must be customizable for different sources, destinations & Services, The option should be available in GUI Device should support Static routing, RIP, OSFF,BCP, IS-IS, RIPng, OSFF-3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000- signatures		÷ .
 web filtering, Intrusion prevention system, Traffic shaping, etc. The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 70 Mbps IPSec VPN throughput. Should support 70 Mbps NGFW Throughput. The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory integration The device should have FS protection for 6000-signatures 		
 The platform must be capable of supporting a minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway to Gateway and 200Client-to-Gateway IPSec VPN Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic. Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT64, IPv6 IPSEC VPN Should Support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BCP, IS-15, RIPng, OSPF/3 and BCP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000t signatures 		
 minimum of 5 interfaces with auto sensing 10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway to-Gateway and 200Client-to-Gateway IPSec VPN throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT64, IPv6 IPSEC VPN Should Support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-15, RIPng, OSPF 3 and BGP44. Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		shaping, etc.
10/100/1000 capability The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to-Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic. Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic. NAT46, NAT64, IPv6 IPSEC VPN Should Support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPFV3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for Goot+ signatures		The platform must be capable of supporting a
The Firewall must support at least 800,000 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to-Gateway and 200Client-to-Gateway IPSec VPN throughput. The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
 concurrent connections and 12,000 new sessions second The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to-Gateway and 200Client-to-Gateway IPSec VPN throughput. The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should Support IPV6 functions such as Management over IPv6. IPv6 Forting protocols, IPv6 tungling, firewall and UTM for IPv6 traffic, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & & Stervices. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
 second The Firewall should be having minimum 900 Mbps throughput. Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway to Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & &services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPF/3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
The Firewall should be having minimum 900 Mbps throughput Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway-to Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support for authentication for Users and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
 throughput Should support 70 Mbps IPSec VPN throughput, Should support 150Gateway to Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GU1 Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
 Should support 70 Mbps IPSec VPN throughput. Should support 150Gateway to Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
 Should support 150Gateway to Gateway and 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP seesion flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
 200Client-to-Gateway IPSec VPN Tunnels The firewall should support a minimum of atleast 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
 250 Mbps of IPS & 150 Mbps NGFW Throughput. Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures 		
Test condition should be real-world / enterprise mix traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 fouting protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP Syn flood, TCP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
traffic. The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell		
The firewall should support a minimum 100 Mbps Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF, BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Threat protection throughput on Realworld or Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Enterprise Traffic Mix traffic Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Device should support Virtualization (ie Virtual Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Systems / Virtual Domains). Please mention what is the maximum number of virtual instances supported Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Should support more than one ISP link with automatic ISP link failover as well as ISP link load sharing for outbound traffic.Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPNShould support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUIDevice should support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+)Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
automatic ISP link failover as well as ISP link load sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		the maximum number of virtual instances supported
sharing for outbound traffic. Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Should Support IPv6 functions such as Management over IPv6, IPv6 routing protocols, IPv6 tunnelling, firewall and UTM for IPv6 traffic, NAT46, NAT64, IPv6 IPSEC VPN Should support IPv4 and IPv6 Rate based DOS protection with threshold settings against TCP Syn flood, TCP/UDP/ port scan, ICMP sweep, TCP/UDP/ SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures	\sim	
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		÷.
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		IPv6 IPSEC VPN
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		Should support IPv4 and IPv6 Rate based DOS
SCTP/ICMP session flooding. Threshold settings must be customizable for different sources, destinations & services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
must be customizable for different sources, destinations &services. The option should be available in GUIDevice should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+)Support for Native Windows Active Directory and Novell eDirectory IntegrationThe device should have IPS protection for 6000+ signatures		
destinations &services. The option should be available in GUI Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Device should support Static routing, RIP, OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures	<i>y</i>	
OSPF,BGP, IS-IS, RIPng, OSPFv3 and BGP4+ Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		available in GUI
Support for authentication for Users and Firewall Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		Device should support Static routing, RIP,
Administrators (Local and Remote – RADIUS, LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
LDAP & TACACS+) Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Support for Native Windows Active Directory and Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
Novell eDirectory Integration The device should have IPS protection for 6000+ signatures		
The device should have IPS protection for 6000+ signatures		
signatures		
		-
	18 The Calicut Co. operation	

	Should Identify and control over 2500+ applications (ie Application control feature)
	Gateway AV should be supported for real-time
	detection of viruses and malicious code for
	HTTP, HTTPS, FTP, SMTP, SMTPS, POP3, POP3S,
	IMAP, IMAPS, IM and SMB
	Antivirus module should support Advanced Threat
	Protection (ATP). It should be having an option to
	submit suspicious files to External cloud-based file analysis (OS sandbox) for threat detection
	Should support Gateway Data Loss Prevention
	(DLP) feature for popular protocols like HTTP,
	HTTPS, FTP, POP3, IMAP, SMTP, POP3S, IMAPS,
	SMTPS with Document Fingerprinting.
	The security device should be having cloud
	application access control function. Example
	allowing gmail access but restricts attachment upload
	download option or disable youtube video upload
	option.
	The security appliance should be having configurable
	option to quarantine source address if that address tries to download infected file.
	The security appliance should be having configurable
	The security appliance should be having comiguration
	option to quarantine attack generating source address
	OEM should be having the following
	OEM should be having the following certifications/Ratings
	OEM should be having the following
	OEM should be having the following certifications/Ratings a. OEM should be ICSA Labs Advanced Threat
	OEMshouldbehavingthefollowingcertifications/Ratingsa. OEMshouldbeICSALabsAdvancedThreatDefensecertified
	OEM should be having the following certifications/Ratingshaving the following followinga. OEM should be ICSA Labs Advanced Threat Defense certifiedhere is a structureb. OS should be "IPv6 Phase II Ready" certified
0	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4
	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certified
· cut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and
icut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs certified.
aicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs and VB100 certified
calicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs and VB100 certifiedf. Antivirus should ICSA Labs and VB100 certifiedg. OEM should be having "Recommended" rating in
calicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs certified.f. Antivirus should ICSA Labs and VB100 certified g. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and
calicut co	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs and VB100 certifiedf. Antivirus should ICSA Labs and VB100 certifiedg. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and Next Generation Firewall testing.
ne calicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs certified.f. Antivirus should ICSA Labs and VB100 certifiedg. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and Next Generation Firewall testing.h. OEM should be rated as Leader or Challenger in
ne calicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs and VB100 certifiedf. Antivirus should ICSA Labs and VB100 certifiedg. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and Next Generation Firewall testing.
ne calicut	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs certified.f. Antivirus should ICSA Labs and VB100 certified g. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and Next Generation Firewall testing.h. OEM should be rated as Leader or Challenger in the Gartner magic quadrant for Enterprise Firewall
ne calicult	OEM should be having the following certifications/Ratingsa. OEM should be ICSA Labs Advanced Threat Defense certifiedb. OS should be "IPv6 Phase II Ready" certifiedc. Firewall module should be ICSA Labs and EAL 4 certifiedd. VPN should be ICSA Labs certified for both IPSec and SSL-TLSe. Network Intrusion Prevention System (NIPS) and should be ICSA Labs certified.f. Antivirus should ICSA Labs and VB100 certified g. OEM should be having "Recommended" rating in NSS Labs network intrusion prevention testing and Next Generation Firewall testing.h. OEM should be rated as Leader or Challenger in the Gartner magic quadrant for Enterprise Firewall and UTM

4.1.4. Group D : 5 KVA Online UPS with Batteries

Sl. No.	Category	Description	Nos.
01.	Input		1
	Voltage Range	160 - 300 VAC @ 100% load (Single Phase with	

	ground)
Frequency Range	45 to 55 Hz
Power Factor	≥ 0.99 at full load and nominal input Voltage
Isolation Transformer	Built in at the input side of the UPS
Output	
Output	Sine wave, 230 VAC + / - 1%, 50 Hz \pm 0.1 Hz (Free
Voltage and Waveform	Since wave, 250 V/RC + 7 = $1/0$, 50 Hz \pm 0.1 Hz (Field Running Mode)
Frequency	
(Synchronisation Mode)	45 to 55 Hz
Harmonic Distortion	45 10 55 112
(THD)	\leq 3% (linear load), \leq 5% (non-linear load)
Crest Factor	$\leq 5\%$ (mean road), $\leq 5\%$ (non-intear road)
Efficiency (AC - AC)	>90%
Power Factor	
Power Factor	0.8 Lagging
Oracita d	105% - 110% for 10 minutes, 131% - 150% for 10
Overload	Seconds
Battery	
Detterre T	28000VAH using 12V EXIDE EL+ TUBULAR for
Battery Type	4 hours backup minimum
DC Voltage	5KVA (192VDC to 240VDC)
	Over Voltage Cut off Device 3 seconds, Converter
	Mode (CVCF)
	ECO Mode, Configurable Bypass Parameters, Cold
	Start, Auto Re-start,
Features	Polarity protection for battery connection
Display	LCD – User friendly display.
Charging Profile	2 stage charging (Constant Current / Float Charge)
Temperature	
Compensated charger	Available
Fan type	Intelligent Fan Operation, Speed Control
Controller	Micro Controller Unit
Bypass Voltage 💦 🔿	
Tolerance	170V - 264V (adjustable in front panel)
Bypass Frequency Sync	47.5Hz - 52.5Hz
	configration via web browser, NMS,JAVA
	Applet, Telnet SNMP or, Hyper terminal, this
	technology provides reliable automatic event
Advanced	notification, via, E mail, SMS*,WAP*, and SNMP
Communciation	trap.
Electrical	Input Breaker, Input Terminal Block,
Output Socket	6 x Indian Type 6A, Terminal Block
Battery Terminal	ANEN 2 Poles
ECO Mode	97.00%
DC /AC Efficiency	
(Inverter),	
@ rated load	90.00%
Noise Level	50dBA
	0 - 40 deg C (with full Load), 40.1 to 50 deg -
Operating Temperature	De-rated to 20%
Standards (Certificate to	
be enclosed)	IP-20, EN 62040-1, EN 62040-2, IEC 62040-3
· · · · · · · · · · · · · · · · · · ·	CE Certified, ISO 9001 : 2008 , 14001 : 2004, BS
Certifications (certificate	CE Certified, ISO 9001 : 2008, 14001 : 2004, BS

	BIS up to 5kva, ROHS	
	should be available locally	
Service centre	(proof to be provided)	
	Battery Rack should be provided (Racks as per	
	requirement of bank)	
warranty	3yeras for UPS and 4 years batteries	

4.1.5. Group E : Other Peripherals

Sl.	Category	Description			
No.					
01.	12 U Network Rack	Make : Cyber Rack / NetRack / APW President			
		Additionals			
		Power Strip - 2			
		Tray - 1			
		Rack Mounting Kit – 2			
		With 3 Years Onsite Comprehensive			
		Manufacturer's Warranty			
02.	Biometric Attendance	Make: ESSL	2		
	Device – ESSL	Software for Biometric working			
		Also Integrate with ESSL Device with our Head			
		Office			
		With 3 Years Onsite Comprehensive			
		Manufacturer's Warranty			
03.	Webcam – Logitech	With 3 Years Onsite Comprehensive	8		
	C170	Manufacturer's Warranty			
04.	Scanner – Canon Lide	With 3 Years Onsite Comprehensive	1		
	220	Manufacturer's Warranty			
		0			

4.1.6. Group F : Barcode Printers & Scanners

Sl.	Category	Description	Nos.
No.		Description	105
05.	Barcode Printer	Up to 250 mm/sec print Speed	3
		8 dots/mm Print Resolution	
		80 or 58 +0/-1 mm Paper Width	
		64 mm (512 dots/line, default) Printing Width	
		6KB Input Buffer	
	\sim	LED indicator Power; Error; Paper out	
		Auto cutter	
· · · · · ·		USB(True USB /Virtual COM selectable)	
		+Serial +LAN	
		Software for Prepare Barcode	
		With 3 Years Onsite Comprehensive	
		Manufacturer's Warranty	
06.	Barcode Scanner	2 x red LED Light source	3
		CMOS array sensor Scan Method	
		752 (H) x 480 (V) pixels Resolution	
		Depth of Field - 40~120 mm (15 mils QR	
		code)	
		Scan Angle -Horizontal -41° , Vertical -26°	

Up to 60 fps Scan Rate 1D Barcode Support : JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBNISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey 2D Barcode Support : Aztec Code, Aztec Runes, Chinese Sensible code, Codablock F,	
Composite codes, Data Matrix (ECC200/EC0- 140), Maxi Code (mode 2~5), MicroPDF41, QR & Micro-QR Code, PDF417 Interface USB (CD-3200U) & RS232 (CD- 3200R) Scanner stand With 3 Years Onsite Comprehensive Manufacturer's Warranty	<u>ک</u>

4.1.7. Group G : LCD Television

4.1.7. Group G : LCD Television				
Sl.	Category Description			
No.				
01.	20" LCD TV with wall mounting kit.	With 3 Years Onsite Comprehensive Manufacturer's Warranty	1	
02.	43" LCD Commercial Display Panel with roof mounting kit.	Display Should Commercial graded, Panel Size: 43-inch widescreen or higher, Type: IPS LED, Resolution: Full HD (1,920 x 1,080 pixels). Brightness: 350 cd/m2 or higher, back light scanning: 100Hz or above, Viewing Angle (H/V): 178°/178° (CR 10), Inputs: HDMI x 2, USB2.0 x1, Video: RCAx1, Audio in (L/R): RCA x2, VGA x1, RS-232Cx1, Sound Output: 20W (10W + 10W), Power Consumption: 75W or less. Functions required: Built in USB Media player. Std. Accessories: Wall mount kit, OEM table top stand, Power cord, remote controller with batteries (AA size x 2), HDMI Cables 5 Meters and installation with necessary cabling. Warranty: Three Years onsite Comprehensive Manufacturer's Warranty	1	

4.1.8. Group H : Passbook KIOSK

Sl. No.	Category	Description	Nos.
01.	Туре	Industrial grade Kiosk	2
	Processor and	Industrial grade mother board with quad core	
	motherboard	processor	
	Touch pad	Industrial grade touch pad with 5,00,000 million	
	i oucli pau	touch life	

Pass Book printer	Integrated
Software	Software required for printing support
Printing Method	Barcode Scanning & Printing
Warranty	With 3 Years Onsite Comprehensive
	Manufacturer's Warranty

4.1.9. Group I : Token Display & Queue Management System

Sl.	C	ategory	Description	Nos.
No.				
01.	Token	Display &	Wifi Token Issuer with Printer	1
	Queue	Management	Wifi Calling Device	0.
	System		Wifi Display with AC Power 🛛 🔨 🐧	
			Charger for wifi unit batteries	
			Wifi Hotspot Creator	

4.2. Warranty Period

This contract will include supply & installation of Desktop Computers & Printers and all other peripherals with 3 years on-site comprehensive warranty and support as per OEM from date of installation. The bidder want to produce the documentary proof the item quoted.

4.3. AMC Rate

The bidder shall submit AMC rate for each items.

4.4. Service response time and mode of service

- **4.4.1.** For complaints not requiring spare parts, the system will be made operational within one working day or two calendar days, whichever is earlier, from the day of complaint is registered.
- **4.4.2.** For complaints requiring spare parts, the system will be made operational within two working day or five calendar days, whichever is earlier, from the day of complaint is registered
- 4.5. Delivery & Installation
- **4.5.1.** The delivery and installation period of the supplies should be within 15 days from the date of confirmed order from CCUB. In case bidder fails to supply or installation within the accepted period, liquidated damages at the rate of 1% of contract value of the order, for per week of delay subject to maximum of 10% of the order value will be levied.

- **4.5.2.** If any delay in delivery the supplier should arrange stand by systems from the date provided by CCUB.
- **4.5.3.** The Delivery place will be communicated by bank to the supplier in time. CCUB have the right to transport any of the items from one branch to another, the supplier required to be provide the support & service at any branch of CCUB.

4.6. Payment Terms

- **4.6.1.** 80% of the price of supplied items shall be paid by the bank on delivery of material in good conditions along with Certificate of receipt.
- **4.6.2.** Balance 20% will be released within 15 days from date of successful installation. The supplier shall provide the signed copy of certificate of installation from our branches.

Payment will be released only on submission of Invoice/Bill duly completed in all respect.

- 4.7. Other Conditions
- **4.7.1.** Any deduction by CCUB on the amount of bill due to any pending issue related to the bill period will be paid after receipt of written confirmation by the contractor that the pending issue has been satisfactory attended to. If the pending issue is not resolved till the subsequent bill is submitted, the same shall not be entertained and adjustments made from further payments of the contractor for which he will be responsible.
- **4.7.2.** The contractor shall be liable for any breach, non-performance or delay in carrying out any obligation contained in the contract. In case a job is not attended within one week of reporting, it may be carried out through some other source at the risk and cost of the contractor, after issue of one written warning.
- **4.7.3.** The contractor shall be responsible for all type of accidents during course of the execution

5. Letter of Acceptance

5.1. Letter of Acceptance.

Every bidder shall submit the attached statement in their letter head, with the Technical bid document submitted by them.

ACCEPTANCE OF CCUB'S TENDER CONDITIONS

- 1. Tender document for supply of Computers, Printer and Other Peripherals has been received from ccub, in direct / website. I/We here by unconditionally accept the tender condition of ccub's tender documents.
- 2. I/We here with submitting the tender documents as requested by ccub, with required processing fee and EMD amounts.
- 3. We here by undertake the responsibility of supply of the items as per the specification mentioned and as per the ccub's conditions.

